HellermannTyton

Technical data sheet

Article number:
111-05441 T50L



Product Group	Cable Ties for higher impact resistant Polyamide 6.6 ScanBlack
Product Family	T-Series in PA66HIR(S)
Material	Polyamide 6.6, high impact modified, scan black (PA66HIR(S))
Colour	Black (BK)

Application Tool	ProCut 9 no battery, EVOcut, MK7P, MK10-SB, MK20, EVO7i, EVO7iSP, EVO9, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	110 mm
Bundle Ø min.	1.5 mm
Flammability	UL 94 HB
Halogen-free	Yes
Length (L)	390 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +80 °C
Package Content	100 pcs.
Package Content packed in	bag
Releasable Closure (Yes/No)	No
Specifications	IEC 62275
Thickness (T)	1.4 mm
Toothing (Serration)	Inside Serrated
UV-resistant acc. to ASTM D6779 (Yes/No)	Yes
Variant	Inside Serrated
Weight/Unit	0.002549 kg
Width (W)	4.6 mm

HF ✓ RoHS ✓

created on 18. September 2026, 6:55 am

Technical changes and errors reserved. It´s up to the customer to check the suitability for a specific application by means of tests.