
VS 29 LG

Stop end, polystyrene, RAL 7035, Pg29





Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

RoHS

Material	Polystyrene, impact resistant
Temp. range min	-20 °C
Temp. range max	60 °C
Protection class	IP56
Advice	with sealing IP66/IP68
Thread type	PG
Ø Connection thread D	29
Length screw-in thread L	8 mm
Total length TL	12 mm
External diameter ED	44 mm
Product Color	RAL 7035
Order no. RAL 7035	50060714
Type	VS 29 LG
Packing unit	100
EAN number	4007685607148
Tariff number	39269097
ETIM-Classification	EC000032


Recommended accessories

MUG 29 LG	10060676
ADR 29	10061425

27.10.2026

Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 🖷 +49-4191-508-209
contact@wiska.de · www.wiska.com

Other technical data on request / subject to change without notice



Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 🖷 +49-4191-508-209
contact@wiska.de · www.wiska.com

Other technical data on request / subject to change without notice